

2-CYLINDER CONCRETE CRUSHERS

for excavators from 1 to 80 ton

Not even the hardest job can withstand the MCK!

- Double motors for an excellent rotation and high power (MCK20 up).
- Double-turn ball bearing (MCK20 up).
- Jaws highly resistant.
- High cutting power.
- Cylinders fully protected from possible debris during demolition.



Find out more



"A" JAW



MCK01



"F" JAW - CRUSHER



"S" JAW - SHEAR

MCK SERIES

Application Fields



NEW

Models	MCK01	MCK03-A	MCK06-A	MCK03-F	MCK06-F	MCK10-F	
Carrier weight	t	1-4	3-9	7-15	3-9	7-15	10-17
Weight	kg	175	300	650	300	650	1200
Closing force	t**	38	50	60	50	60	70
Jaw opening	mm	390	400	680	400	680	780
Jaw depth	mm	400	430	600	430	600	690
Width upper jaw	mm	50	40	45	40	45	50
Height	mm	900	1150	1500	1150	1500	1800
Length of cutting blades	mm	100	100	200	100	200	200
Opening/Closing Pmax	bar*	220	260	320	260	320	320
Flow	l/min	20-50	30-50	70-120	30-50	90-150	70-120
Rotation Pmax	bar	120	100	100	100	140	100
Flow	l/min	10-25	10-30	10-30	10-30	40-60	10-30
Back pressure max.	bar	-	-	-	-	-	-
Cycle time Opening/Closing	sec	1.8/2.5	1.8/2.5	2.2/3.0	1.8/2.5	2.4/3.1	2.2/3.0

Models	MCK03-S	MCK06-S	MCK03-S	MCK06-S
Carrier weight	t	3-9	7-15	3-9
Weight	kg	300	650	300
Closing force	t**	50	60	50
Jaw opening	mm	225	680	225
Jaw depth	mm	430	600	430
Width upper jaw	mm	40	45	40
Height	mm	1220	1680	1220
Length of cutting blades	mm	100	200	100
Opening/Closing Pmax	bar*	260	320	260
Flow	l/min	30-50	70-120	30-50
Rotation Pmax	bar	100	100	100
Flow	l/min	10-30	10-30	10-30
Back pressure max.	bar	-	-	-
Cycle time Opening/Closing	sec	1.8/2.5	2.2/3.0	1.8/2.5

Models	MCK03-S	MCK06-S
Carrier weight	t	3-9
Weight	kg	300
Closing force	t**	50
Jaw opening	mm	225
Jaw depth	mm	430
Width upper jaw	mm	40
Height	mm	1220
Length of cutting blades	mm	100
Opening/Closing Pmax	bar*	260
Flow	l/min	30-50
Rotation Pmax	bar	100
Flow	l/min	10-30
Back pressure max.	bar	-
Cycle time Opening/Closing	sec	1.8/2.5



"A" JAW

All illustrations and numerical data in this catalog are purely indicative and subject to change at our discretion and without notice.
We therefore reserve the right to modify them with a view to improving and continuously developing our product.

2-CYLINDER CONCRETE CRUSHERS

for excavators from 1 to 80 ton

Not even the hardest job can withstand the MCK!

- Double motors for an excellent rotation and high power (MCK20 up).
- Double-turn ball bearing (MCK20 up).
- Jaws highly resistant.
- High cutting power.
- Cylinders fully protected from possible debris during demolition.



USED FOR CUTTING AND CRUSHING CONCRETE WITH STEEL REINFORCEMENT AND FOR CUTTING STEEL STRUCTURES, THE HAMMER CONCRETE CRUSHER HAS BEEN DEVELOPED FOR PRIMARY AND SECONDARY DEMOLITION.



Find out more



"L" JAW-WOOD CUTTER

MCK "F" Crushing kit

- Hydraulic system fully protected by the frame
- Perfect jaws geometry ensures that blades remain sharp longer
- Wearing jaws and blades easily replaceable on site
- Customized jaws are available for every customer need *optional


MCK SERIES

Application Fields



Models	MCK10-A	MCK15-A	MCK15-L	MCK15-F	MCK20-A	MCK25-A	MCK35-A	MCK45-A	MCK60-A	MCK75-A
Carrier weight	t	10-17	14-20	14-20	18-25	20-35	25-45	35-55	50-70	60-80
Weight	kg	1200	1400	1400	2000	2425	3250	4200	5300	6300
Closing force	t**	70	78	78	84	96	108	124	144	160
Jaw opening	mm	780	825	825	1000	1150	1360	1500	1600	1750
Jaw depth	mm	690	780	780	865	935	1335	1135	1235	1350
Width upper jaw	mm	50	55	55	60	70	80	90	100	100
Height	mm	1800	1980	1980	2195	2390	2545	2845	2995	3225
Length of cutting blades	mm	200	200	200	200	250	300	300	300	400
Opening/Closing Pmax	bar*	320	320	320	320	320	320	320	320	320
Flow	l/min	90-150	110-170	110-170	150-250	200-300	250-350	300-500	400-600	500-700
Rotation Pmax	bar	140	140	140	140	140	140	140	140	200
Flow	l/min	40-60	40-60	40-60	40-60	40-60	40-60	40-60	40-60	60
Back pressure max.	bar	-	-	-	-	-	-	-	-	10**
Cycle time Opening/Closing	sec	2.4/3.1	2.3/3.0	2.3/3.0	2.3/3.0	2.5/3.4	3.3/3.6	3.2/3.4	2.8/3.9	2.8/3.8

OPTIONAL MCK10-A: crusher shroud kit MCK10-F



All illustrations and numerical data in this catalog are purely indicative and subject to change at our discretion and without notice. We therefore reserve the right to modify them with a view to improving and continuously developing our product.

2-CYLINDER CONCRETE CRUSHERS

for excavators from 1 to 80 ton

Not even the hardest job can withstand the MCK!

- Double motors for an excellent rotation and high power (MCK20 up).
- Double-turn ball bearing (MCK20 up).
- Jaws highly resistant.
- High cutting power.
- Cylinders fully protected from possible debris during demolition.



"C" JAW

MCK SERIES

Application Fields



Mining & Quarrying



Demolition & Renovation



Construction



Metallurgical Industry



Recycling



Find out more

USED FOR CUTTING AND CRUSHING CONCRETE WITH STEEL REINFORCEMENT AND FOR CUTTING STEEL STRUCTURES, THE HAMMER CONCRETE CRUSHER HAS BEEN DEVELOPED FOR PRIMARY AND SECONDARY DEMOLITION.

- Hydraulic system fully protected by the frame
- Perfect jaws geometry ensures that blades remain sharp longer
- Wearing jaws and blades easily replaceable on site
- Customized jaws are available for every customer need *optional

Models	MCK10-C	MCK15-C	MCK20-C	MCK25-C	MCK35-C	MCK45-C	MCK60-C	MCK75-C
Carrier weight	t	10-17	14-20	18-25	20-35	25-45	35-55	60-80
Weight	kg	1200	1400	2100	2425	3300	4320	6300
Closing force	t**	70	78	84	96	108	124	160
Jaw opening	mm	780	825	1000	1150	1360	1500	1700
Jaw depth	mm	690	780	865	935	1335	1135	1350
Width upper jaw	mm	50	55	60	70	80	90	100
Height	mm	1800	1980	2195	2390	2545	2845	3225
Length of cutting blades	mm	200	200	200	250	300	300	400
Opening/Closing Pmax	bar*	320	320	320	320	320	320	320
Flow	l/min	90-150	110-170	150-250	200-300	250-350	300-500	500-700
Rotation Pmax	bar	140	140	140	140	140	140	200
Flow	l/min	40-60	40-60	40-60	40-60	40-60	40-60	60
Back pressure max.	bar	-	-	-	-	-	-	10**
Cycle time Opening/Closing	sec	2.4/3.1	2.3/3.0	2.3/3.0	2.5/3.4	3.3/3.6	3.2/3.4	2.8/3.8

Models	MCK60-C	MCK75-C	
Carrier weight	t	50-70	60-80
Weight	kg	5440	6300
Closing force	t**	144	160
Jaw opening	mm	1600	1700
Jaw depth	mm	1235	1350
Width upper jaw	mm	100	100
Height	mm	2995	3225
Length of cutting blades	mm	300	400
Opening/Closing Pmax	bar*	320	320
Flow	l/min	400-600	500-700
Rotation Pmax	bar	140	200
Flow	l/min	40-60	60
Back pressure max.	bar	-	10**
Cycle time Opening/Closing	sec	2.8/3.9	2.8/3.8



"C" JAW

All illustrations and numerical data in this catalog are purely indicative and subject to change at our discretion and without notice. We therefore reserve the right to modify them with a view to improving and continuously developing our product.