



STONE CRUSHER WITH FIXED TOOTH ROTOR.

The STCL is the smallest stone crusher FAE makes. It is extremely versatile thanks to it small dimension and lower weight. This makes it suitable for use in orchards and vineyards where stones can emerge due to soil erosion. An adjustable internal counter-blade allows you to obtain the desired final material size. The hydraulically controlled rear door also helps in determining final product size. This attachment also has a specially mounted gearbox so while it sits in a low position, the PTO shaft still sits at an optimal angle.



STANDARD EQUIPMENT

PTO shaft with cam clutch
Gearbox with freewheel
Trasmission with belts in Poly-Chain® Carbon
Hydraulic hood
Flat pressed welded steel counter-blades
Adjustable Hardox® counter-blade
Penetration skids
Enclosed machine body
Inside lateral protection
Dual row protection chains



OPTIONS
Possibility to choose Transmission 540 / 1000 rpm (STCL 125)
Adjustable extended 3 point linkage (STCL/ST)
Hydraulic top link
Dozing blade
Grader blade



Adjustable extended 3 point hitch fits perfectly with any kind of tractor

Enclosed machine body protects internal components

Adjustable Hardox® counter-blade effectively control the final product size

Penetration skids help the machine to better penetrate the soil

MODEL	Tractor hp		PTO (rpm)	Working width	Total width	Weight (kg)	Max shredding diameter	Max working depth	No. teeth type STCL/3 +
	min	max	·	(mm)	(mm)		(mm)	(mm)	C/3/SS
STCL 100	80	120*	540 o 1000	1110	1414	1230	150	150	20+4
STCL 125	80	120*	540 o 1000	1350	1660	1280	150	150	26+4
STCL 150	90	120*	540 o 1000	1590	1900	1440	150	150	32+4
STCL 175	100	120*	540 o 1000	1830	2140	1570	150	150	38+4
STCL/DT 175	100	150	1000	1830	2140	1600	150	150	38+4
STCL/DT 200	120	150	1000	2070	2380	1750	150	150	42+4

Data refers to machine as standard.

The technical data in this catalog may be altered without prior notice.